






# Three Phase String Inverter (LV)

SUN- 6 / 8 K-G03-LV



-  127/220Vac and 60Hz, Three phase system
-  2 MPP tracker, Max. efficiency up to 98.5%
-  Zero export application, VSG application
-  String intelligent monitoring (optional)
-  Wide output voltage range
-  Ani-PID function (Optional)

**Deye**

*Clean Power For You*

Model	SUN-6K-G03-LV	SUN-8K-G03-LV
<b>Input Side</b>		
Max. DC Input Power (kW)	7.8	10.4
Max. DC Input Voltage (V)	800	
Start-up DC Input Voltage (V)	250	
MPPT Operating Range (V)	200~700	
Max. DC Input Current (A)	11+22	
Number of MPPT / Strings per MPPT	2 / 1+2	
<b>Output Side</b>		
Rated Output Power (kW)	6	8
Max. Active Power (kW)	6.6	8.8
Rated AC Grid Voltage (V)	127 / 220	
AC Grid Voltage Range (V)	176Vac~242Vac (this may vary with grid standards)	
Rated Grid Frequency (Hz)	60 / 50 (Optional)	
Operating Phase	Three phase	
Rated AC Grid Output Current (A)	15.7	21
Max. AC Output Current (A)	17.3	23.1
Output Power Factor	0.8 leading to 0.8 lagging	
Grid Current THD	<2%	
DC Injection Current (mA)	<0.5%	
Grid Frequency Range	47~52 or 57~62 (Optional)	
<b>Efficiency</b>		
Max. Efficiency	98.5%	
Euro Efficiency	97.5%	
MPPT Efficiency	>99%	
<b>Protection</b>		
DC Reverse-Polarity Protection	Yes	
AC Short Circuit Protection	Yes	
AC Output Overcurrent Protection	Yes	
Output Overvoltage Protection	Yes	
Insulation Resistance Protection	Yes	
Ground Fault Monitoring	Yes	
Anti-islanding Protection	Yes	
Temperature Protection	Yes	
Integrated DC Switch	Yes	
Remote software upload	Yes	
Remote change of operating parameters	Yes	
Surge protection	DC Type II / AC Type II	
<b>General Data</b>		
Size (mm)	330W×430H×193.5D	
Weight (kg)	17	
Topology	Transformerless	
Internal Consumption	<1W (Night)	
Running Temperature	-25~65°C	
Ingress Protection	IP65	
Noise Emission (Typical)	<45 dB	
Cooling Concept	Smart cooling	
Max. Operating Altitude Without Derating	2000m	
Designed Lifetime	>20 years	
Grid Connection Standard	EN50549, IEC61727, VDE 0126-1-1, IEC62109-1-2	
Operating Surroundings Humidity	0-100%	
Safety EMC / Standard	IEC62109-1/-2, EN61000-6-1, EN61000-6-3	
<b>Features</b>		
DC Connection	MC-4 mateable	
AC Connection	IP65 rated plug	
Display	LCD1602	
Interface	RS485/RS232/Wifi/LAN	